



Designation	Electronic Ballast	Bezeichnung	Elektr. Vorschaltgerät
Order No.	<b>5431414E230MMNB</b>	Bestell Nr.	5431414E230MMNB
Housing	Aluminum	Gehäuse	Aluminium
Mode	Pre-Heat Start	Mode	Warmstart
Connection	Push-in	Anschluss	Push-in
Terminal	Klemme	Wago 250	
Input Voltage	Netzeingangsspannung	220-240 Vac	
Input Frequency	Eingangsfrequenz	50/60 Hz	
Lamp	Lampe	3 x 14W T5	
		4 x 14W T5	
Power Factor	Leistungsfaktor	0,95	
Restart	Neustart	Automatic	
Protection	Sicherung	EOL	
Total Harmonic Dist.	Harmonische	< 15%	
Working Temperature	Betriebstemperatur	0°C - +50°C	
Max. Case Temperature	Max. Gehäusetemperatur	75°C	
Length	Länge	280 mm	
Width	Breite	39 mm	
Height	Höhe	21 mm	
Weight	Gewicht	< 300 g	
Electrical Class	Schutzklasse	I	
Efficiency	Effizienz	EEI = A2 Class	
Approval Standard	Zertifizierung	CE, TÜV	
Regular Standard	Standards	Meets CISPR15 for EMI / RFI	
		EN 61000-3-2 Class C	
		Compliance to: EN61547	
Offer Quantity	Angebotsmenge	200, 300-500, >500	